



## INSTALLATION AND MAINTENANCE ADVICE

**SERIES:**

LANE

**NOMINAL SIZE:**

7.9X16 PORCELAIN STONEWARE

**USE:**

floors  
walls  
indoors  
outdoors

**INSTALLATION:**

The material is deliberately shaded. Take the material from several boxes and mix carefully.

**RECOMMENDED ADHESIVE:**

Adhesive for porcelain stoneware

**RECOMMENDED JOINT:**

2 millimetres

**RECOMMENDED FILLERS:**

cement-based grout / epoxy grout

**CLEANING AT THE END OF THE WORK:**

**CEMENT-BASED GROUT:** Buffered acid (e.g. DETERDEK PRO by FILA or similar). Wet the floor with water, dilute the product 1:5 with water and pour it on the floor. Wait for 2-3 minutes then use a white scotch brite pad and rinse well with clean water.

**EPOXY GROUT:** Alkaline detergent (e.g. FILA CR10 by FILA). FILA CR10: apply pure, wait for 30 minutes then use a green scotch brite pad.

**SILICONE:** Solvent for silicone e.g. FILA ZERO SIL. Put it straight onto the stain, wait for 20 minutes and remove the mark using scotch brite.



**PAINT:** Can usually be removed using water, but if resin-based paints or particular enamels have been used, it is best to ask the manufacturer which solvent is most suitable.

**RUST:** stain remover es. FILA NO RUST. Apply the product onto the stain, leave for 15 minutes, remove the residue and rinse thoroughly.