

BOURGOGNE

Made in Italy

Inspired by natural limestone
High Definition texture & pattern
Superior Technical performance



AVAILABLE COLOURS

Porcelain



Minimal Blanc




Minimal Beige



Minimal Gris


AVAILABLE SIZES



NATURALE

Blanc
Gris

1200x2780 X 6.5mm



NATURALE

Blanc
Beige
Gris

TECHNICA GRIP

Beige

1200x1200 x 9mm




NATURALE

Blanc
Beige
Gris

TECHNICA GRIP

Blanc
Beige
Gris



NATURALE

Blanc
Beige


1000x1000 x 9mm



NATURALE

Blanc
Beige
Gris


600x600x 9mm



NATURALE

Blanc
Beige
Gris

300x600x 9mm



V3

MODERATE VARIATION

Minimal Beige



TECHNICAL DATA



Porcelain Tiles
ISO 13006 Annex G - UNI EN 14411 Annex G - Bla GL
ANSI A137.1 - CLASS P1

CARATTERISTICHE TECNICHE		NORMA	VALORI		
Technical Features - Caracteristiques Techniques - Technische Eigenschaften Technische Eigenschaften - Caracteristicas Tecnicas - Технические Характеристики		Standard - Norme Norm - Norma - Норма	Value - Valeur Vorgabe - Valor - Средние		
	ASSORBIMENTO D'ACQUA Water absorption - Absorption d'eau - Wasseraufnahme Absorción de agua - Поглощение воды	UNI EN ISO 10545/3 ASTM C373	Conforme Compliant		
	RESISTENZA ALLA FLESSIONE Modulus of rupture - Resistance à la flexion - Biegefestigkeit Resistencia a la flexion - Прочность на изгиб	SPESSORE UNI EN ISO 10545/4	6,5 mm	9 mm	20MM
	FORZA DI ROTTURA Breaking strength - Résistance à la rupture - Bruchlast Resistencia a la rotura - Разрывное усилие	UNI EN ISO 10545/4 ASTM C648	≥ 700 N ≥ 175 lbf	≥ 2000 N ≥ 400 lbf	≥ 12000 N ≥ 2500 lbf
	RESISTENZA AL GELO Frost resistance - Résistance au gel - Frostbeständigkeit Resistencia a las heladas - Морозостойкость	UNI EN ISO 10545/12 ASTM C1026	Conforme Unaffected		
	RESISTENZA CHIMICA AD ALTE E BASSE CONCENTRAZIONI DI ACIDI E BASI Chemical resistance to high and low acid and basic concentrations Résistance chimique aux hautes et basses concentrations d'acides et de bases Chemikalienfestigkeit bei hohen und niedrigen Konzentrationen von Säuren und Basen Resistencia química con concentraciones altas y bajas de ácidos y bases Химическая стойкость к высоким и низким концентрациям кислот и щелочей	UNI EN ISO 10545/13 ASTM C650	A - LA - HA Unaffected		
	RESISTENZA ALLE MACCHIE Stain resistance - Résistance aux taches - Fleckenbeständigkeit Resistencia a las manchas - Стойкость к образованию пятен	UNI EN ISO 10545/14 ASTM C1378	5 Class A		
	COEFFICIENTE DI ATTRITO Slip resistance Coefficient de glissement Rutschfestigkeit Barfußbereich Coeficiente de atrito medio Коэффициент трения		NATURALE	LAPPATO ANTIQUE	TECNICA / 20MM
		DIN EN 16165 Annex B	R10	-	R11
		DIN EN 16165 Annex A	B (A+B)	-	B (A+B)
		ANSI A326.3:2017 DCOF	WET ≥ 0,50	-	WET ≥ 0,65
		B.C.R.A. D.M. N. 236 14/6/89	> 0,40	-	> 0,40
		AS 4586-2013 Anexo A	P2	-	P4
		BS 7976-2: 2002 BSEN13036-4:2011 Pendulum testers	< 36 Moderate Slip potential	-	> 36 Low Slip potential
		UNE 41901:2017 EX DB SUA (actual)	-	-	3

Per maggiori chiarimenti sui dati tecnici e sulla garanzia consultare il catalogo generale in vigore. - For further information on technical specifications, please consult our up-dated general catalogue. - Pour toutes informations supplémentaires sur les données techniques et sur les garanties, veuillez consulter le catalogue général en vigueur. - Für weitere Informationen über technische Daten und Garantie beziehen sie sich bitte auf den aktuellen Gesamtkatalog. - Para ulteriores informaciones sobre los datos técnicos y la garantía, vease el catalogo general en vigor. - Более подробную информацию о технических данных и гарантии смотрите в действующем сводном каталог.



PRODUCT CERTIFIED
FOR LOW CHEMICAL
EMISSIONS:
ULCOM/UG
UL 2818



CONTACT

visit one of our showrooms to view this collection
www.dilorenzo.com.au



Information provided in this catalogue is accurate at time of publication. Colours shown may vary to the actual tile, therefore we recommend you view these tiles in one of our showrooms